

TACTYLE CR™

www.cordovasafety.com

SHELL CONSTRUCTION

- TACTYLE CR™, 18-Gauge
- HPPE/Tungsten Steel Shell
- Reinforced Thumb Crotch
- Touchscreen Fingertips

COATING

- TUF-COR™ Nitrile Coating

PERFORMANCE INFORMATION

- ANSI/ISEA 105-2016
- Cut Level A9
- Abrasion Level 4
- Puncture Level 4



DESCRIPTION:

TACTYLE™ CR: 18-Gauge, HPPE/Tungsten Steel Shell, TUF-COR™ Nitrile Coating, ANSI/ISEA 105-2016 Cut Level A9: 6690

TACTYLE™ CR: 18-Gauge, HPPE/Tungsten Steel Shell, TUF-COR™ Nitrile Coating, Reinforced Thumb Crotch, Touchscreen Fingertips

CERTIFICATIONS & RATINGS:

Component Materials comply with all federal regulations for food contact. (U.S. Code of Federal Regulations, 21CFR, Parts 170-199)

APPLICATIONS:



GLASS HANDLING



RECYCLING OPERATIONS



PLASTIC EXTRUSION



METAL FABRICATION

CARE:

Wash using warm water and commercial laundry detergent. Water temperature not to exceed 50°C/122°F. Air-dry or tumble-dry with low heat.

ORDERING:

Unit of Sale: One Pair
Packaging: 12 Prs/Polybag
Case Pack: 144 Pairs
COO: China
Available Sizes: S-2XL

Case Weight (lbs)	S	M	L	XL	XXL
	22.90	23.40	26.50	28.70	30.90

BARCODES:

ITEM	DOZEN	CASE
6690S	796326040201	50796326040206
6690M	796326040218	50796326040213
6690L	796326040225	50796326040220
6690XL	796326040232	50796326040237
6690XXL	796326040249	50796326040244

Corporate Headquarters:

4025 Viscount Avenue
 Memphis, TN 38118
 Phone 800.458.8763
 Fax 901.458.3343

CORE SAFETY PROTECTION

www.cordovasafety.com

West Coast Office:

433 Cheryl Lane (Dock Door 14)
 City of Industry, CA 91789
 Phone 909.590.2679
 Fax 909.590.3130